

TITLE OF THE INVENTION

INFORMATION MANAGEMENT APPARATUS, INFORMATION OUTPUT
SYSTEM, PORTABLE TERMINAL, AND INFORMATION OUTPUTTING METHOD

BACKGROUND OF THE INVENTION5 Field of the Invention

[0001]

The present invention relates to an information output
apparatus, an information output system, a portable terminal
for use in the information output system, and information
10 outputting method, in which an object and the information
of the same are connected with each other on a
three-dimensional space to achieve an output service for
information of the object with the aid of a virtual drag
and drop operation.

15 Related Background Art

[0002]

Many systems for realizing services for outputting
information have been proposed until now. Since these
services are often provided generally in relation to an object,
20 it is desired to provide a system for providing information
associated with the object.

[0003]

Hereupon, there are known a variety of techniques to
instruct to have a predetermined processing applied on
25 certain data on a computer. A technique called "drag and
drop" is known as one of these techniques. In the technique

"drag and drop", data to be processed is dragged and dropped on an icon for signifying a predetermined processing, whereby the predetermined processing is executed on the predetermined data. Herein, the drag means "selecting and moving" executed using chiefly a pointing device such as a mouse. The drop means the release of the selection of data having been selected using a mouse, which is realized in many cases by releasing a button of the mouse generally.

[0004]

For example, when a certain file is desired to be printed, a mouse cursor is moved onto an icon indicative of the file, and a mouse button is depressed to "select" the file, and further the mouse is moved as it is to achieve the "drag" operation. The file is moreover moved onto an icon indicative of a printer, and then the mouse button is released to achieve the drop operation. With such a processing, a service, "print" is provided for the "file".

[0005]

Reference 1 discloses a technique wherein a three-dimensional icon is moved onto a virtual space on a computer with the drag and drop operation, and the three-dimensional icon is displayed on the virtual space. Reference 2 discloses a technique wherein a three-dimensional object is moved onto a virtual space on a computer with the drag and drop operation. With this technique, a plurality of users share the virtual space on the computer.

[Reference 1] Japanese Patent Publication Laid-Open
No.H11-053581

[Reference 2] Japanese Patent Publication Laid-Open No.
2002-049934

5 SUMMARY OF THE INVENTION

[0006]

As disclosed in references 1 and 2, there are
conventionally known a drag and drop operation in a computer
and a drag and drop operation on a virtual space in a computer.

10 [0007]

Such a drag and drop operation is a convenient technique
to link a "service" to an "object", so that it is preferable
to realize such a drag and drop operation even on a real
three-dimensional space.

15 [0008]

However, for a drag and drop operation on a real
three-dimensional space any effective technique is not yet
known.

[0009]

20 In view of the drawbacks with the prior art, it is an
object of the present invention to provide an information
output apparatus, an information output system, a portable
terminal for use in the information output system, and a
information outputting method, wherein a drag and drop
25 operation on a real three-dimensional space is realized,
and for example information relevant to goods can be printed

with a printer.

[0010]

An information management apparatus according to the present invention provides:

5 output apparatus information storage means for storing information relevant to an output apparatus for outputting information, with the stored information linked with identification information for identifying the output apparatus;

10 output request receiving means for receiving an output request for information transmitted from a portable terminal;

 inquiry signal transmission means for transmitting an inquiry signal for inquiring said portable terminal of an output apparatus for an output destination, when an output request is received by the output request receiving means;

15 image data receiving means for receiving image data transmitted from the portable terminal;

 identification information acquisition means for analyzing image data transmitted from the portable terminal in response to the inquiry signal and received by the image data receiving means, and for acquiring identification information relevant to an output apparatus involved in the image data;

20 output destination information retrieval means for retrieving the information relevant to the output apparatus from the output apparatus information storage means based

upon the identification information acquired by the
identification information acquisition means; and

information output means for, based upon the
information relevant to the particular output apparatus
5 retrieved by the output destination information retrieval
means, outputting the information to the particular output
apparatus.

[0011]

Therefore, the information management apparatus
10 performs acquiring the identification information involved
in the image data transmitted from the portable terminal,
retrieving an output apparatus being a destination to be
outputted from the output information storage means on the
basis of the identification information, and outputting the
15 information from the output apparatus on the basis on the
information retrieved. Hereby, a user can specify the
desired output apparatus being a destination to be outputted,
with photographing the identification information of the
output apparatus, and transmitting it to the information
20 management apparatus.

[0012]

The aforementioned information management apparatus
may be further provide:

goods information storage means for storing
25 information relevant to goods, with the stored information
linked to identification information for identifying the

goods;

identification information acquisition
means for analyzing image data received by the image data
receiving means, and for acquiring identification
5 information of goods involved in image data; and

goods information retrieval means for retrieving the
information relevant to the goods from the goods information
storage means based upon the identification information
acquired by the identification information acquisition means,
10 wherein,

the information output means outputs the information
relevant to the goods retrieved by the goods information
retrieval means.

[0013]

15 Thus, the information management apparatus performs
acquiring the identification information involved in the
image data transmitted from the portable terminal, retrieving
an output apparatus being a destination to be outputted from
the goods information storage means on the basis of the
20 identification information, and outputting the information
retrieved. Hereby, a user can output the information of the
goods with photographing the identification information of
goods desired to know detailed information, and transmitting
the identification information of the goods to the
25 information management apparatus. Moreover, the information
management apparatus performs specifying an output apparatus

being a destination to be outputted, so that a user can output
the goods information from the output apparatus, with
photographing the identification information of the
apparatus after photographing the identification
5 information of the goods, and can output information with
realizing the drag and drop operation in a real
three-dimensional space.

[0014]

10 An information management apparatus according to the
present invention provides:

information storage means for storing information
relevant to an output apparatus for outputting information,
with the stored information linked to global identification
information tagged uniformly to the output apparatus and
15 different kinds of goods;

output request receiving means for receiving an output
request of information transmitted from a portable terminal;

20 inquiry signal transmission means for transmitting an
inquiry signal for inquiring said portable terminal of an
output apparatus for an output destination, when an output
request is received by the output request receiving means;

image data receiving means for receiving image data
transmitted from the portable terminal;

25 identification information acquisition means for
analyzing image data transmitted from the portable terminal
in response to the inquiry signal and received by the image

data receiving means, and for acquiring identification information relevant to an output apparatus involved in the image data;

5 converting means for converting identification information of the output apparatus acquired by the identification information acquisition means into global identification information;

10 information retrieval means for retrieving information relevant to the output apparatus from the information storage means based upon the global identification information converted by the converting means; and

15 information output means for, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval means, outputting the information to the particular output apparatus.

[0015]

20 The information management apparatus is thus further adapted such that the identification information involved in the image data transmitted from the portable terminal is acquired, on the basis of which the information of the output apparatus being an output destination is retrieved from the information storage means, on the basis of which
25 the information is outputted from the output apparatus. A user can hereby specify the output apparatus being an output

destination, and output the information. Herein, the
"global identification information" refers to one for
uniformly treating varieties of pieces of identification
information used globally generally. In accordance with the
5 present invention, the information storage means can
uniformly treat various apparatuses and goods because it
stores information while linking it to such global
identification information.

[0016]

10 The aforementioned information management apparatus
may provide:

 the information storage means further stores
information relevant to goods , with the stored information
linked to the global identification information;

15 the identification information acquisition means
analyzes image data received by the image data receiving
means, and acquires identification information of goods
involved in the image data;

 the converting means converts identification
20 information of goods acquired by the identification
information acquisition means into global identification
information;

 the information retrieval means retrieves information
relevant to the goods from the information storage means
25 based upon the global identification information converted
by the converting means; and

the information output means outputs information relevant to goods retrieved by the information retrieval means.

[0017]

5 The information management apparatus is thus adapted such that the identification information involved in the image data transmitted from the portable terminal is acquired, on the basis of which information relevant to goods is retrieved from the goods information storage means, and the
10 retrieved goods information is outputted. A user can output the information of goods, detailed information of which is desired to be known, by photographing the identification information of the goods, and transmitting it to the information management apparatus. Further, the information
15 management apparatus is adapted such that an output apparatus being an output destination can be specified by photographing the identification information of the output apparatus serving to output goods information, and transmitting it to the information management apparatus. A user can output
20 the goods information from the output apparatus by photographing the identification information of the goods, and then photographing the identification information of the output apparatus, and can therefore output information by realizing a drag and drop operation in a real
25 three-dimensional space. In the present invention, since the information storage means has stored information while

linking it to the global identification information,
varieties of apparatuses and goods can be uniformly treated.

[0018]

An information management apparatus according to the
5 present invention provides:

output apparatus information storage means for storing
information relevant to an output apparatus for outputting
information , with the stored information linked to
identification information for identifying the output
10 apparatus;

output request receiving means for receiving image data
transmitted from a portable terminal and an output request
for information;

identification information acquisition means for
15 analyzing the image data received by the output request
receiving means, and for acquiring identification
information of an output apparatus involved in the image
data;

output destination information retrieval means for
20 retrieving the information relevant to the output apparatus
from the output apparatus information storage means based
upon the identification information acquired by the
identification information acquisition means; and

information output means for, based upon the
25 information relevant to the particular output apparatus
retrieved by the output destination information retrieval

means, outputting the information to the particular output apparatus.

[0019]

5 The information management apparatus is thus adapted
such that the identification information involved in the
image data transmitted from the portable terminal is acquired,
on the basis of which the information of the output apparatus
being an output destination is in turn retrieved from the
output information storage means, on the basis of which the
10 information is outputted from the output apparatus. A user
can hereby specify the output apparatus being the output
destination to output the information by photographing the
identification information of the output apparatus,
information of which is thereupon desired to be outputted,
15 and transmitting it to the information management apparatus.
A user can further reduce the number of times of transmission
and reception between the portable terminal and the
information management apparatus by receiving the image
information for specifying the output destination together
20 with the output request.

[0020]

A portable terminal including photographing means
according to the present invention provides:

25 output request transmission means for transmitting an
output request for information to an information management
apparatus which allows an output apparatus to output the

information;

inquiry signal receiving means for receiving an inquiry
signal transmitted from the information management apparatus
in response to the output request for inquiring said portable
5 terminal of an output apparatus for an output destination;
and

image data transmission means for transmitting
identification information tagged to the output apparatus
for identifying this particular output apparatus and image
10 data photographed with the photographing means to the
information management apparatus, when an inquiry signal
is received by the inquiry signal receiving means.

[0021]

In the portable terminal including the photographing
15 means for the inquiry signal from the information management
apparatus the identification information of the desired
output apparatus is photographed to transmit the image data.
Hereby, the output apparatus being an output destination
can be specified.

20 [0022]

In the foregoing portable terminal, the image data
transmission means may transmit identification information
tagged to goods for identifying this particular goods and
image data photographed with the photographing means to the
25 information management apparatus.

[0023]

In the portable terminal including the photographing means as described above, the identification information of goods, detailed information of which is desired to be known, is photographed, and the image data is transmitted, whereby a desired goods can be specified.

[0024]

A portable terminal according to the present invention provides:

photographing means for photographing identification information to obtain image data, the identification information being tagged to an output apparatus for identifying this particular output apparatus; and

output request transmission means for transmitting image data photographed by the photographing means and an output request for information to an information management apparatus which allows to output information.

[0025]

The portable terminal is adapted as described above such that the identification information of a desired output apparatus is photographed, and the image data is transmitted. Hereby, the output apparatus of an output destination can be specified.

[0026]

An information output system according to the present invention provides the foregoing information management apparatus and the foregoing portable terminal.

[0027]

The information output system provides the information management apparatus and the portable terminal is adapted as described above. Hereby, the output apparatus of an output destination for information can be specified by transmitting the imager data. Further, the identification information of the output apparatus is photographed after image data of the identification information of goods is transmitted, and the image data is transmitted. Hereby, the goods information can be outputted from the output apparatus, and hence a drag and drop operation in a real three-dimensional space can be realized, and the information can be outputted.

[0028]

An information output system according to the present invention has an output apparatus for outputting information and an information management apparatus connecting each other through a network, in which the information management apparatus includes an output apparatus information storage means for storing information relevant to the output apparatus and identifies an output apparatus based on information transmitted from a portable terminal to have this particular output information, wherein,

the portable terminal provides:

identification acquisition means for acquiring

identification information of the output apparatus; and

identification information transmission means for

transmitting identification information acquired by the
identification information acquisition means to the
information management apparatus, and

the information management apparatus provides:

5 identification information receiving means for
receiving identification information transmitted from the
portable terminal;

 output destination information retrieval means for
retrieving information relevant to the output apparatus from
10 the output apparatus information storage means based upon
identification information received by the identification
information receiving means; and

 information output means for, based upon the
information relevant to the particular output apparatus
15 retrieved by the output destination information retrieval
means, outputting the information to the particular output
apparatus.

[0029]

 The portable terminal is adapted to comprise the
20 identification information acquisition means, and the
identification information of the output apparatus acquired
by the identification information acquisition means is
transmitted, as described above. Hereby, the information
output destination can be specified with ease.

25 [0030]

 In the information output system, the identification

information acquisition means included in the portable terminal is preferably means for acquiring the identification information of the output apparatus with the aid of the output apparatus and proximate distance radio communication. As the method for the proximate distance radio communication with the use of high frequency and infrared rays is useable. Further, communication may be allowed using the Bluetooth.

[0031]

An information outputting method in an information output system according to the present invention having an output apparatus for outputting information and an information management apparatus connecting each other through a network, in which the information management apparatus includes an output apparatus information storage means for storing information relevant to the output apparatus and specifies an output apparatus to output information based upon information transmitted from a portable terminal, provides:

an output request transmission step for transmitting an output request for information from the portable terminal to the information management apparatus receiving it;

an inquiry signal transmission step for transmitting an inquiry signal which the information management apparatus inquires an output apparatus being a destination to be outputted, to the portable terminal receiving it, when the information management apparatus receives the output request

in the output request transmission step;

an image data transmission step for transmitting image data of identification information tagged to an output apparatus for identifying it, photographed by the portable terminal, when the portable terminal receives the inquiry signal in the inquiry signal transmission step;

identification information acquisition step for analyzing image data received by the information management apparatus in the image data transmission step, and for acquiring the identification information of the output apparatus involved in the image data;

an output destination information retrieval step for retrieving the information relevant to the output apparatus from the output apparatus information storage means using the information management apparatus, based upon the identification information acquired in the identification information acquisition step; and

an information output step for allowing the output apparatus to output information using the information management apparatus, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval step, outputting the information to the particular output apparatus.

[0032]

The identification information involved in the image data transmitted from the portable terminal is acquired,

on the basis of which the information of the output apparatus
being an output destination from the output information
storage means is retrieved, on the basis of which the
information is outputted from the output apparatus. A user
5 hereby can specify an output apparatus being an output
destination, and output information by photographing the
identification of an output apparatus to which information
is desired to be outputted, and transmitting it to the
information management apparatus.

10 [0033]

An information outputting method in an information
output system according to the present invention having an
output apparatus for outputting goods information and an
information management apparatus connecting each other
15 through a network, in which the information management
apparatus includes an output apparatus information storage
means for storing information relevant to the output
apparatus and goods information storage means for storing
information relevant to goods, and specifies an output
20 apparatus to output information based upon information
transmitted from a portable terminal, provides:

a first image data transmission step for transmitting
image data of identification information tagged to goods
for identifying it, photographed by the portable terminal,
25 to the information management apparatus receiving it;

a first identification information acquisition step

for analyzing image data received by the information management apparatus in the first image data transmission step, and for acquiring the identification information of the goods involved in the image data;

5 goods information retrieval step for retrieving the information relevant to the goods from the goods information storage means using the information management apparatus, based upon the identification information acquired in the first identification information acquisition step;

10 an output request transmission step for transmitting an output request for the information relevant to the goods using the portable terminal to the information management apparatus receiving it;

 an inquiry signal transmission step for transmitting
15 an inquiry signal for inquiring said portable terminal of an output apparatus for an output destination, from the information management apparatus to the portable terminal receiving it, when the information management apparatus receives the inquiry signal in the output request
20 transmission step;

 a second image data transmission step for transmitting
 image data of identification information tagged to an output
 apparatus for identifying it, photographed by the portable
 terminal, to the information management apparatus receiving
25 it, when the portable terminal receives the inquiry signal
 in the inquiry signal transmission step;

a second identification information acquisition step for analyzing image data received by the information management apparatus in the second image data transmission step, and for acquiring the identification information of the goods involved in the image data;

an output destination information retrieval step for retrieving the information relevant to the output apparatus from the output apparatus information storage means using the information management apparatus, based upon the identification information acquired in the second identification information acquisition step; and

an information output step for outputting the information relevant to the goods, retrieved in the goods information retrieval step, using the information management apparatus, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval step, outputting the information to the particular output apparatus.

[0034]

The identification information involved in the image data transmitted from the portable terminal is acquired, on the basis of which the information relevant to goods from the goods information storage means is retrieved, and the retrieved information of the goods is outputted, as described above. A user can hereby output the information of the goods by photographing the identification information of goods,

detailed information of which is desired to be known, and transmitting it to the image management apparatus. Further, since an output apparatus being an output destination can be specified by photographing the identification information of an output apparatus for outputting goods information, and transmitting it to the information management apparatus, a user can output the goods information from the output apparatus by photographing the identification information of goods and then photographing the output apparatus. Hereby the user can output the information by realizing a drag and drop operation in a real three-dimensional space.

[0035]

A information outputting method in an information output system according to the present invention having an output apparatus for outputting information and an information management apparatus connecting each other through a network, in which the information management apparatus includes an information storage means for storing information relevant to the output apparatus, linking global identification information uniformly tagged to any output apparatus and to different kinds of goods, and specifies an output apparatus to output information based upon information transmitted from a portable terminal, provides:

an output request transmission step for transmitting an output request for information from the portable terminal to the information management apparatus receiving it;

an inquiry signal transmission step for transmitting an inquiry signal which the information management apparatus inquires an output apparatus being a destination to be outputted, to the portable terminal receiving it, when the information management apparatus receives the output request in the output request transmission step;

an image data transmission step for transmitting image data of identification information tagged to an apparatus for identifying it, photographed by the portable terminal, when the portable terminal receives the inquiry signal in the inquiry signal transmission step;

an identification information acquisition step for analyzing image data received by the information management apparatus in the image data transmission step, and for acquiring the identification information of the output apparatus involved in the image data;

a converting step for converting the identification information of the output apparatus, acquired in the identification information acquisition step, into the global identification information;

an information retrieval step for retrieving the information relevant to the output apparatus from the information storage means using the information management apparatus, based upon the global identification information converted in the converting step; and

an information output step for allowing the output

apparatus to output information using the information management apparatus, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval step, outputting the information to the particular output apparatus.

[0036]

The identification information involved in the image data transmitted from the portable terminal is acquired, on the basis of which the information of an output apparatus being an output destination from the information storage means is retrieved, on the basis of which information is outputted from the output apparatus, as described above. A user can output the information by specifying the output apparatus being an output destination by photographing the identification information of an output apparatus to which the information is outputted, and transmitting it to the information management apparatus. Herein, "global identification information" refers to identification information for uniformly processing varieties of identification information used widely in the world. According to the present invention since the information storage means stores information linking it to the global identification information, various apparatuses and goods can be uniformly treated.

[0037]

An information outputting method in an information

output system according to the present invention having an
output apparatus for outputting information and an
information management apparatus connecting each other
through a network, in which the information management
5 apparatus includes an information storage means for storing
information relevant to the output apparatus and to goods,
linking global identification information uniformly tagged
to any output apparatus and to different kinds of goods,
and specifies an output apparatus to output information based
10 upon information transmitted from a portable terminal,
provides:

a first image data transmission step for transmitting
image data of identification information tagged to goods
for identifying it, photographed by the portable terminal,
15 to the information management apparatus receiving it;

a first identification information acquisition step
for analyzing image data received by the information
management apparatus in the first image data transmission
step, and for acquiring the identification information of
20 the goods involved in the image data;

a first converting step for converting identification
information of the goods acquired in the first identification
information acquisition step into global identification
information;

25 a first information retrieval step for retrieving the
information relevant to the goods from the information

storage means using the information management apparatus,
based upon the global identification information converted
in the first converting step;

an output request transmission step for transmitting
5 an output request for the information relevant to the goods
using the portable terminal to the information management
apparatus receiving it;

an inquiry signal transmission step for transmitting
an inquiry signal, for inquiring said portable terminal of
10 an output apparatus for an output destination, from the
information management apparatus to the portable terminal
receiving it, when the information management apparatus
receives the inquiry signal in the output request
transmission step;

15 a second image data transmission step for transmitting
image data of identification information tagged to an output
apparatus for identifying it, photographed by the portable
terminal, to the information management apparatus receiving
it, when the portable terminal receives the inquiry signal
20 in the inquiry signal transmission step;

a second identification information acquisition step
for analyzing image data received by the information
management apparatus in the second image data transmission
step, and for acquiring the identification information of
25 the output apparatus involved in the image data;

a second converting step for converting the

identification information of the output apparatus acquired in the second identification information acquisition step into global identification information;

5 a second information retrieval step for retrieving the information relevant to the output apparatus from the information storage means using the information management apparatus, based upon the global identification information converted in the second converting step; and

10 an information output step for outputting the information relevant to the goods, retrieved in the first information retrieval step, using the information management apparatus, based upon the information relevant to the output apparatus retrieved in the second information retrieval step.

[0038]

15 The identification information involved in image data transmitted from the portable terminal is acquired, on the basis of which information relevant to goods from the goods information storage means is retrieved, and the retrieved information is outputted, as described above. A user can
20 acquire the information of the goods by photographing the goods, detailed information of which is desired to be known, and transmitting it to the information management apparatus. Further, since an output apparatus being an output
25 destination can be specified by photographing the identification information of an output apparatus for outputting the goods information, and transmitting it to

the information management apparatus, a user can output the goods information from the output apparatus by photographing the identification information of the goods, and then photographing the apparatus, and hence can output the information by realizing a drag and drop operation in a real three-dimensional space. In accordance with the present invention, since the information storage means stores information linking it to the global identification information, varieties of apparatuses and goods can be uniformly treated.

[0039]

A information outputting method in an information output system according to the present invention having an output apparatus for outputting information and an information management apparatus connecting each other through a network, in which the information management apparatus includes an output apparatus information storage means for storing information relevant to the output apparatus and specifies an output apparatus to output information based upon information transmitted from a portable terminal, provides:

an image data photographing step for obtaining image data of identification information tagged to an output apparatus identifying it, photographed by the portable;

an output request transmission step for transmitting the image data photographed in the image data photographing

step and an output request for information, from the portable terminal to the information management apparatus receiving them;

5 an identification information acquisition step for analyzing the image data transmitted in the output request transmission step, and for acquiring the identification information of the output apparatus involved in the image data;

10 an output destination information retrieval step for retrieving the information relevant to the output apparatus from the output apparatus information storage means, based upon the identification information acquired in the identification information acquisition step; and

15 an information output step for outputting the information to the output apparatus, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval step, outputting the information to the particular output apparatus.

20 [0040]

25 The identification information involved in the image data transmitted from the portable terminal is acquired, on the basis of which the information of an output apparatus being an output destination is retrieved from the output information storage means, on the basis of which information is outputted from the output apparatus, as described above.

A user can hereby output the information by specifying the output apparatus being the output destination by photographing the identification information of an output apparatus to which the output is desired to be outputted, and transmitting it to the information management apparatus. Further, the number of times of transmission and reception between the portable terminal and the information management apparatus can be reduced.

[0041]

A information outputting method according to the present invention having an output apparatus for outputting information and an information management apparatus connecting each other through a network, in which the information management apparatus includes an output apparatus information storage means for storing information relevant to the output apparatus and specifies an output apparatus to output information based upon information transmitted from a portable terminal, provides:

an identification information acquisition step for acquiring identification information of the output apparatus using the portable terminal acquires;

an identification information transmission step for transmitting the identification information acquired in the identification information acquisition step, from the portable terminal to the information management apparatus;

an output destination information retrieval step for

retrieving the information relevant to the output apparatus from the output apparatus information storage means using the information management apparatus, based upon the identification information transmitted in the

5 identification information transmission step; and

an information output step for outputting the information to the output apparatus, based upon the information relevant to the particular output apparatus retrieved by the output destination information retrieval step, outputting the information to the particular output apparatus.

[0042]

Hereby, the information output destination can be specified with ease by acquiring the identification information by the portable terminal in the identification information acquisition step, and transmitting the identification information of the output apparatus to the information management apparatus in the successive identification information transmission step as describe above.

[0043]

It is preferable in the aforementioned information output method to acquire the identification information of the output apparatus by permitting the portable terminal to undergo near distance radio communication with the output apparatus. As the near distance radio communication there

is useable communication with the use of high frequency and infrared rays. Additionally, communication is assured using the Bluetooth.

[0044]

5 The present invention will become more fully understood from the detailed description given herein below and the accompanying drawings which are given by way of illustration only, and thus are not to be considered as limiting the present invention.

10 Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way
15 of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

20 [0045]

Fig. 1 is a view illustrating the construction of an information output system associated with an embodiment.

Fig. 2 is a view illustrating the construction of a store information apparatus.

25 Fig. 3 is a view illustrating the construction of a management server.

Fig.4 is a view of example illustrating data stored in a database.

Fig.5 is a flow chart illustrating the operation of the information output system.

5 Fig.6 is a flow chart illustrating the operation of the information output system.

Fig.7 is a view of example illustrating another example of the information output system.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 [0046]

In what follows, there will be described a preferred embodiment of an information output system according to the present invention with reference to the accompanying drawings. Same symbols of components described herein as those of same components as those in the description of the accompanied drawings shall be applied thereto, and overlapped description therefore will be omitted.

[0047]

20 As an exemplary information output system 1, there will be described a system for outputting the information of goods sold at a store (bag store) 8. Referring to Fig. 1, there is provided a block diagram illustrating the information output system 1 associated with the present embodiment. The information output system 1 comprises a management server 25 30 for managing information, a store information apparatus 20, a portable terminal 14 possessed by a user U, and a printer

40 for printing and outputting information. A
two-dimensional bar code 12a representative of an ID of goods
12 sold at the store 8 is tagged to the goods 12, and a
two-dimensional bar code 40a representative of an ID of a
5 printer 40 installed in the store 8 is tagged to the printer
40. The store information apparatus 20 and the management
server 30 in the present embodiment constitute an
"information management apparatus" defined in the claims
of the present invention. In the following, respective
10 components constituting the information output system 1
associated with the present embodiment will be described.

[0048]

Referring to Fig. 2, there is illustrated the
construction of the store information apparatus 20. The
15 store information apparatus 20 comprises communication means
20a, control means 20b, and printing means 20c.

[0049]

The communication means 20a serves to communicate with
the portable terminal 14 of the user U and the management
20 server 30. For the communication means 20a there are useable
direct communication to the portable terminal 14 by the near
distance radio technique such as the Bluetooth and a technique
to communicate with the portable terminal 14 via internet
by connecting to Internet capable of intercommunication with
25 the portable terminal 14.

[0050]

The control means 20b, when receiving image data transmitted from the portable terminal 14 by the communication means 20a, serves to endow the ID of the store information apparatus 20 to the image data, and transmit
5 back it to the communication means 20a. The image data tagged with the ID is transmitted to the management server 30 with the aid of the communication means 20a.

[0051]

The printing means 20c, when receiving a printing
10 instruction transmitted from the management server 30 through the communication means, serves to output information to the printer 40 based upon the printing instruction. The printing means 20c and the printer 40 may be connected through wire or radio communication.

15 [0052]

Referring to Fig. 3, there is illustrated the construction of the management server 30. The management server 30 comprises communication means 30a, recognition means 30b, conversion means 30e, retrieval means 30c, and
20 a database 30d.

[0053]

The data base 30d stores the information of an article and the information of a service. These pieces of the information are stored after being linked with a global ID.
25 The "global ID" signifies an ID for uniformly treating varieties of IDs widely used in the world. For example, for

books an ID called an ISBN is widely used, and for bar codes an ID system called a JAN code is used. Since varieties of IDs are used in the world in such a manner, the global ID is defined in the information output system 1 associated with the present embodiment in order to uniformly treat varieties of IDs. Varieties of articles such as books, vegetables, bags, stores, hotels, and airplanes can be uniformly treated with use of the global ID. Fig. 4 illustrates an example of data stored in the database 30d. As illustrated in the figure in the data base 30d data such of "global ID", "name", and "relevant information" are stored as found in the example in Fig. 4, the data base 30d stores information of a handbag A and relevant information concerning a printer B. More specifically, the data base 30d stores various pieces of information about goods access information associated with apparatuses for providing services.

[0054]

The communication means 30a serves to communicate with the store information apparatus 20. For the communication means 30a there can be adopted varieties of conventional communication techniques. For example, it may be radio communication or wire communication using optical fibers and the like.

[0055]

The recognition means 30b recognizes image data

received from the store information apparatus 20 through the communication means 30a, and recognizes an ID represented by a two dimensional bar code involved in the image. More specifically, it serves to analyze the image data to acquire the ID involved in the image data. In the example illustrated in Fig. 1, there are acquired an ID 12a of the handbag 12 and an ID 40a of the printer 40. Although the recognition means 30b is means for recognizing a value indicated by an original two dimensional bar code from an image of a two dimensional bar code, for such recognition means 30b there can be adopted a technique for use in a prior art two dimensional bar code system. It is typically preferable to recognize a two dimensional bar code using a pattern recognition technique for a two dimensional image. It is noticed that when the communication means 30a receives not image data but an ID itself or a global ID itself, processing by the recognition means 30b is not execute.

[0056]

The conversion means 30e serves to convert an ID recognized by the recognition means 30b to a global ID and output it to the retrieval means 30c. The conversion means 30e has a conversion table referred to upon conversion of a local ID and a global ID defined for every goods.

[0057]

The retrieval means 30c serves to retrieve the data base 30d as an IFD key converted and inputted through the

conversion means 30e, and extract one or more of relevant pieces of information. The retrieval means 30c transmits extracted relevant information to the store information apparatus 20 through the communication means 30a.

5 [0058]

There will be described the portable terminal 14. The portable terminal 14 is a terminal comprising photographic means and communication means. The photographic means has the same functions as those of a still camera, a video camera, and a TV telephone, and the communication means can transmit and receive image data. Particularly, provided that the portable terminal serves likewise a video camera capable of photographing a moving image, when a resolution is low, and photographing conditions are bad, a good image can be selected from a plurality of images photographed in a time series, and images can be synthesized to improve reading accuracy for an ID. Provided that it serves likewise a TV telephone, it is preferable because a response whether or not an ID is correctly read can be returned immediately. Although a typical example of the portable terminal 14 is a portable telephone, such an apparatus as a PDA (Personal Digital Assistant) may be good.

10
15
20

[0059]

There will be described the operation of the information output system 1 associated with the present embodiment, and an information output method associated with the same

25

embodiment. Figs. 5 and 6 are flow charts each illustrating the operation of the information output system 1 associated with the present embodiment. In an example described below, there will be described the case where a user U enters a bag store, and make output information concerning handbag arranged in the store 8.

[0060]

Fig. 5 will first be referred to for the description. There is photographed using photographing means of a portable telephone the two dimensional bar code 12a attached to goods, detailed information of which is desired to be known, here the handbag 12 arranged in the bag store 8 (S10).

[0061]

The portable terminal 14 transmits the photographed image data to the store information apparatus 20 (S12), and instructs the indoor information apparatus 20 to acquire information relevant to the handbag 12 (a request for requiring information). Thereupon, the portable terminal 14 may tag the image data with an ID of the portable terminal 14, and transmit it to the store information apparatus 20.

[0062]

The store information apparatus 20, once receiving the image data transmitted from the portable terminal 14, transfers the image data to the management server 30 (S14). In more detail, the store information apparatus 20, once detecting tat the communication means 20a receives the

information acquiring request involving the aforementioned image data, tags the received image data with the ID of the store information apparatus 20 with the aid of the control means 20b, and transfers the image data to the management server 30 (S14).

[0063]

Successively, the management server 30 receives the image data transferred from the store information apparatus 20 (S14), and recognizes the ID involved in the received image data (S18). Then, the management server 30 converts the recognized ID from the image data to a global ID through the conversion means 30e (S20), retrieves the data base 30d employing the converted global ID as a key, and acquires the information relevant to the handbag 12 from the data base 30d (S22).

[0064]

The management server 30 transmits the acquired data relevant to the handbag 122 (goods data) to the store information apparatus 20 with the aid of the communication means 20a (S24), and the store information apparatus 20 transfers the receive goods data from the management server 30 to the portable terminal 14 (S26). The store information apparatus 20 selects only a service available at the store 8 in the detailed information received from the management server 30 with the aid of the control means 20b, and transmits only the information relevant to the selected service to

the portable terminal 14 of the user U. For example, even when there is transmitted information relevant to a handbag made of alligator in Italy, and guaranteed for one year with the price of ¥10,000 (refer to Fig. 4.) from the management server 30, it is possible not to select data relevant to the price of ¥10,000 when the handbag 12 is sold at a discount in the bag store 8. In the present embodiment, since the information management apparatus is constructed, divided into the two sections of the indoor information apparatus 20 and the management server 30, and the detailed information transmitted from the management server 30 is selected by the store information apparatus 20, a service provider can judge what service is actually provided using the store information apparatus, and select the detailed information. More specifically, the management server 30 collectively manages all pieces of information relevant to goods, and the store information apparatus 20 employs the information for each store while customizing it. The management server 20 is hereby useable in itself for another service, and can deal with various services.

[0065]

The portable terminal 14 receives goods information transmitted from the store information apparatus 20 (S28), and displays the received goods information (S30). It displays also a menu of "output service" for outputting the displayed information together with the goods information.

[0066]

Fig. 6 is referred to for the further description. Then, once the user U selects the "output service" displayed in the portable terminal 14 (S32), the portable terminal 14 transmits the information output request to the store information apparatus 20 (S34). The store information apparatus 20, once receiving the output request transmitted from the portable terminal 14 (S36), transmits an inquiry signal for inquiring to which printer 40 information is outputted to the portable terminal 14 (S38). The portable terminal 14, once receiving the inquiry signal transmitted from the store information apparatus 20, displayed on the portable terminal 14 that it has received the inquiry signal, and instructs the user U select the printer 40 being an output destination. More specifically, it instructs the user U to photograph a two dimensional bar code tagged on the printer 40 being an output destination (S40). Further, the portable terminal 14 transmits the photographed image data to the store information apparatus 20 (S42).

[0067]

Once the store information apparatus 20 detects that the communication means 20a has received the image data transmitted from the portable terminal 14 through the control means 20b, the control means 20b transfers the image data received by the communication means 20a to the management server 30 (S44). Successively, the management server 30

receives the image data transmitted from the store
information apparatus 20 through the communication means
20a (S46). The management server 30, once receiving the image
data transmitted from the store information apparatus 20
5 (S46), instructs the recognition means 30b to recognize an
ID involved in the image data (S48), and converts the
recognized ID to a global ID through the conversion means
30e (S50). Then, the management server 30 retrieves the
database 30d using the converted global ID as a key, and
10 acquires information (printer information) relevant to the
printer 40 from the database 30d (S52).

[0068]

The management server 30 transmits the retrieved
printer information to the store information apparatus 20
15 (S54). The store information apparatus 20, once detecting
the reception of the printer information transmitted from
the management server 30 (S56), instructs the printing means
20c to print out goods information based upon the received
printer information (S58). The printer information
20 involves a protocol for accessing the printer 40, a paper
size capable of outputting the number of colors capable of
outputting, and the address of the printer 40.

[0069]

In accordance with the information output system 1 and
25 the information output method associated with the present
embodiment, a user photographs the ID40a of the goods 12

from which information is desired to be acquired, and
photographs the ID 40a of the printer 40, information of
which is desired to be outputted. Hereby, it is possible
to realize the operation property as if the drag and drop
operation is executed on a three-dimensional space.

[0070]

Although there were described above the embodiments
of the present invention with respect to the information
output system and the information output method, the present
invention is not limited thereto.

[0071]

Although in the aforementioned embodiment the image
data of the ID of the printer 40 was transmitted from the
portable terminal 14 in response to the inquiry signal
transmitted from the store information apparatus 20, the
timing when the portable terminal 14 transmits the image
data of the ID of the printer 40 is not limited to that after
the inquiry signal was received. For example, the image
information of the ID of the printer 40 may be transmitted
together with the image information of the ID of the handbag
12. With such a construction it is possible to reduce the
number of times of the transmission/reception of data between
the store information apparatus 20 and the portable terminal
14.

[0072]

Although in the aforementioned embodiment there was

described the example where the detailed information for the handbag 12 in a bag store was acquired, it is also possible to apply the information output system 1 and the information output method according to the present invention to other goods, for example any article sold in stores such as telephones and table services. More specifically, provided that a two dimensional bar code is tagged to these goods, the same operation as that in the aforementioned embodiment can be executed.

[0073]

Although in the aforementioned embodiment there was described the example where two-dimensional bar codes are employed as the ID 12a of the goods 12 and the ID 40a of the printer 40, the present invention is not limited to the two-dimensional bar code. It is also preferable to utilize bar codes commonly used at present, the so-called RF-IDs. The RF-ID can usually store a predetermined amount of information therein, and can know the information from the outside in a non-contact manner. Use is made of an ID as this information, which is useable for the present invention. Although In the case of a general bar code the bar code may be photographed with photographing means provided on the portable terminal 14, the bar code may be read by mounting a bar code reader on the portable terminal 14. As other examples excepting such IDs reading for characters by an OCR, and reading for trademarks and signboards are applicable

to the present invention.

[0074]

Although in the aforementioned embodiment there was described the example of a bag store, the present invention
5 is further applicable to cases where a plurality of stores are assembled such as in a shopping place. The present invention may be applicable also to pleasure grounds and parks.

[0075]

10 Although in the present invention it is generally convenient on the operation that "an object to be outputted" and "a printer to output" are located close to each other, it is not necessarily required that both must be located in the neighborhood. In most extreme case, a printer to
15 output may not exist at a place where an object to be outputted exists. For example, it may allow the printer in an office to output information at another place such as a business. In this situation, there is provided a mechanism for photographing a two-dimensional bar code of the printer 40
20 in an office, or there is stored a two-dimensional bar code information of the printer 40 in an office in storage means in which image information of an ID photographed in the past is stored as a history. By making use of its information it can be outputted to a printer existent at a remote place.
25 Further, if there is provided storage means for storing an ID photographed in the past, it is convenient that

photographing is not required every time of frequently outputting from a printer in a close place.

[0076]

Although in the aforementioned embodiment the store information apparatus 20 is arranged in the store 8, and the management server 30 is provided separately from the store 8, the management server 30 and the store information apparatus 20 may be constructed in a united manner. This will be described with reference to Fig. 7. Fig. 7 illustrates an example of merging the management server 30 and the store information apparatus 20 as a united information management apparatus 50. There may be constructed the information management apparatus 50 which comprises as illustrated in Fig. 7 a data base 30d for storing information of goods and the printer 40, retrieval means 30c for retrieving the data base 30d, recognition means 30b for recognizing an ID from image data, conversion means 30e for converting the ID recognized by the recognition means 30b to a global ID, communication means 20a for communication with the portable terminal 14, and printing means 20c for instructing the printer 40 to print and output information. With such a construction, goods information can be outputted to the designated printer 40 based upon image data transmitted from the portable terminal 14 likewise the information output system 1 associated with the aforementioned embodiment. In the aforementioned embodiment, the information management

apparatus 50 illustrated in Fig. 7 is divided into two components 20, 30 as the store information apparatus 20 and the management server 30.

[0077]

5 Further, in the aforementioned embodiment the store information apparatus 20 has a function as an intermediate with the management server 30 with respect to retrieval for goods information, and a function to print on the basis of print information transmitted from the management server
10 30. Independent apparatuses may achieve each of these two functions respectively. For example, another information apparatus for performing a print service may achieve printing function or another print service site on an Internet may be utilized. The construction is an example of the function
15 of the information management apparatus 50 illustrated in Fig. 7 being divided further finer. It is possible in such a manner to freely change how the function of the information management apparatus 20 is divided and constructed.

[0078]

20 Although in the aforementioned embodiment information of goods and the printer 40 is stored in the database 30d linking with a global ID, it is not necessarily required to employ such a global ID. Any information may be stored linking it to an ID defined for every goods and the printer
25 40. When the global ID is not used, a database may be provided for storing related information for every kind of goods.

[0079]

Although in the aforementioned embodiment there was described as a method for acquiring the identification information of a printer the method for photographing an ID tagged to a printer with the photographing means of the portable terminal, there is considered another method for acquiring identification information. For example, identification information of a printer may be acquired by performing communication between the printer and the portable terminal using high frequency waves and infrared rays. It is possible to specify a printer being an information output destination by transmitting the acquired identification information from the portable terminal to the store information apparatus.

[0080]

From the invention thus described, it will be obvious that the embodiments of the invention may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended for inclusion within the scope of the following claims.